

+ FICHA TÉCNICA

+ CALIBRE	+ DIÁMETRO		+ ÁREA TRANS. (mm ²)	+ PESO (Kg/m)	+ RENDIMIENTO (m/Kg)	+ RESISTENCIA A LA TENSIÓN (KgF/mm ²)
	(mm)	(pulg)				
8.0	4.11	0.162	13.30	0.104	9.6	54-64
8.5	3.94	0.155	12.19	0.095	10.5	55-64
9.0	3.76	0.148	11.10	0.087	11.5	58-72
9.5	3.60	0.142	10.18	0.080	12.5	58-72
10.0	3.43	0.135	9.24	0.072	13.9	63-75
10.5	3.25	0.128	8.30	0.065	15.4	64-75
11.0	3.05	0.120	7.30	0.057	17.4	65-78
11.5	2.87	0.113	6.47	0.051	19.7	65-78
12.0	2.67	0.105	5.60	0.044	22.8	70-82
12.5	2.51	0.099	4.95	0.039	25.7	70-82
13.0	2.32	0.091	4.23	0.033	30.4	72-85
13.5	2.18	0.086	3.73	0.029	34.0	75-85
14.0	2.03	0.080	3.23	0.025	39.5	74-89
14.5	1.93	0.076	2.92	0.023	43.6	76-90
15.0	1.83	0.072	2.63	0.021	48.6	77-90
15.5	1.70	0.067	2.27	0.018	56.3	77-90
16.0	1.57	0.062	1.93	0.015	65.5	78-93